

## LAROX VALVE MODEL SELECTION

PVE	100	AK	10	-	2	0	3	L	R
TYPE	SIZE (DN)	ACTUATOR	PRESSURE CLASSES (PN)	-	FLANGE DRILLINGS	BODY MATERIAL	SHAPE OF FLANGE	OPENING TAGS	AUXILIARIES
PV = open	25-1000	M=handwheel	1= 1 bar		1 = -	0 = Cast iron / Welded steel	types 1 - 4	L = opening tags	Q = quick exhaust valve  R= inductive limits  S= magnetic proximity limits  T= mechan. limits  Z= solenoid valve  X = must be specified
PVE = enclosed		A=pneumatic	6 = 6 bar		2 = DIN PN 10		Determined by the valve manufacturer		
PVS = sealed		AB=with manual override	10 = 10 bar		3 = DIN PN 16	1 = -			
PVE/S = enclosed/sealed			16 = 16 bar		4 = DIN PN 25	2 = AISI 316			
		AK=with el.pneum. positioner	25 = 25 bar		5 = DIN PN 40	3 = aluminium			
			40 = 40 bar		6 = ANSI 150	4 = other			
		AN=with pneum. positioner	64 = 64 bar		7 = ANSI 300	5 = plastic			
			AU=with pneum. spring	100=100 bar		8 = BS TABLE D			
		AV=with mech. spring				9A = AS TABLE D			
						9B = AS TABLE E			
	H=hydraulic		9C = JIS 10						
HP=with hydraulic positioner			9D = JIS 16						
	E=electro mechanical		Other on request						
EO=electric for control									

